


LED
TECHNOLOGY

50,000 Hours Life, 10 Watt, 120VAC, 90CRI



Applications:

4" Recessed Can Kit,
Indoor And Damp Locations Use



Features:

- Adjustable CCT 3000K, 4000K and 5000K
- Replace Incandescent Save 80% Energy (75 Watt Equivalent)
- Instant Bright, High Power LED Bulb
- Smooth Dimming to 10% or Below
- Dims on Most Standard Household Dimmers
- Fits Standard 4 Inch Recess Cans
- Comes with Standard Quick Connect Plug
- Flicker Free, Tested for No Buzzing
- High Efficacy 90CRI True Color



Specification:

Input Line Voltage:	120VAC
Input Power	10W
Input Line Frequency	60Hz
Lamp Life (Rated)	50,000hrs
Minimum Starting Temp	-20°C/-4°F
Maximum Operating Temp	40°C/104°F
Adjustable CCT	3000K/4000K/5000K
CRI	≥90
Lumens	800
Beam Angle	95°
CBCP	400
Dimmable	Standard Triac Dimmer

Height	E Avg/E Max	Beam Angle 90° Deg	Diameter
1m	177.9, 398.21x		200.00cm
2m	44.49, 99.551x		400.00cm
3m	19.77, 44.241x		600.00cm
4m	11.12, 24.891x		800.00cm
5m	7.118, 15.931x		1000.00cm
6m	4.943, 11.061x		1200.00cm
7m	3.631, 8.1261x		1400.00cm
8m	2.780, 6.2221x		1600.00cm
9m	2.197, 4.9161x		1800.00cm
10m	1.779, 3.9821x		2000.00cm

Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

WARRANTY

2-YEAR*

Model:#	Description	wattage	lumens	Socket
LC10RT4-B/CCT	4 Inch Dimmable, Baffled Retrofit Can Kit CCT	10W	800	E26

* 2 Year Limited Warranty Damp Locations Rated This Luminaire is JA8-2019 Compliant

UPC:80680215609-5