

LED
TECHNOLOGY


50,000 Hours Life, 24 Watt, 120VAC, 90CRI

Applications:

8" Recessed, Down Light with J-Box
Indoor And Outdoor Wet Locations Use


Features:

- Adjustable CCT 3000K, 4000K, and 5000K
- Replace Incandescent Save 80% Energy (150 Watt Equivalent)
- Rated Life of 50,000 Hr
- Smooth Dimming to 10%
- Dims on Most Standard Household Dimmers
- IC Rated
- Flicker Free
- High Efficacy 90CRI True Color
- Knockout for Romex or Flex Connection



Specification:

Input Line Voltage:	120VAC
Input Power	24W
Input Line Frequency	60Hz
Lamp Life (Rated)	50,000hrs
Minimum Starting Temp	-20°C/-4°F
Maximum Operating Temp	40°C/104°F
Adjustable CCT	3000K/4000K/5000K
CRI	≥90
Lumens	1800
Beam Angle	110°
CBCP	630
Dimmable	Standard Triac Dimmer



Height	E Avg/E Max	Beam Angle 108.75° Deg	Diameter
1m	197.5, 639.71lx		279.12cm
2m	49.38, 159.91lx		558.23cm
3m	21.95, 71.07lx		837.35cm
4m	12.34, 39.98lx		1116.46cm
5m	7.90, 25.59lx		1395.58cm
6m	5.48, 17.77lx		1674.70cm
7m	4.03, 13.05lx		1953.81cm
8m	3.08, 9.95lx		2232.93cm
9m	2.43, 7.89lx		2512.04cm
10m	1.97, 6.39lx		2791.16cm

Note: The curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

WARRANTY
2-YEAR*

Model:#	Description	wattage	lumens	Socket
LC24RT8-NCBX/CCT	8 Inch Dimmable, LED Down Light With J-Box, 3CCT	24W	1800	N/A

* 2 Year Limited Warranty Wet Locations Rated This Luminaire is JAS Compliant UPC: 80680215608-8